# Operating Instructions



### 20 CU' Refrigerator

G-Series Reach-In Refrigerator/Self Contained Model # G10010 Full Height Door Right Hinge

### NEEDS TO BE TRANSPORTED UPRIGHT. NEEDS TO BE PLUGGED INTO A DEDICATED 20 AMP OUTLET.

#### **Standard Product Features**

- Microprocessor Control with LED Temperature Readout
- Top Mounted, Balanced, Self-Contained Refrigeration System
- Large High Humidity Evaporator Coil Outside the Food Zone
- Full-Length Stainless-Steel Doors with Locks
- Self-Closing Doors with Stay Open Feature At 120°
- Automatically Activated Incandescent Lights
- 9' Cord & Plug attached, 115 volts, 20 amps
- 6" High Casters with Locks
- Length 35", Width 30", Height 83 ¼"
- The light turns on when the door opens
- Shelves set up to hold 20 sheet trays or ten plus food pans

#### **Specifications**

- The standard operating temperature is 34-38° Fahrenheit
- Has Fahrenheit or Celsius Temperature Scale Display Capability
- Recommended load limit per shelf should not exceed 225 lbs.

| DIMENSIONAL DATA      | 1-SECTION MODEL             |
|-----------------------|-----------------------------|
| Net Capacity          | 24.2 cubic feet (686 cu. l) |
| Length                | 29 %" (75.9 cm)             |
| Depth                 | 35 (88.8 cm)                |
| Depth (over the body) | 32 (81.3 cm)                |
| Door Width            | 21 %" (53.6 cm)             |
| Full Door Height      | 57 %"                       |
| Height                | 88 ¼" (211.5 cm)            |
| Full Load             | 4.7 amperes                 |
| Gross Weight          | 395 lbs. (179 kg)           |

## For any questions or concerns, be sure to contact us immediately. Thank you for your business!

1155 Route 9 Wappingers Falls, NY



1 Precision Road Danbury, CT (203) 744-2295

www.durantspartv.com