



Wappingers Falls, NY
(845) 298 - 0011
1155 Route 9
Wappingers, NY 12590

Danbury, CT
(203) 744 - 2295
98 1/2 Mill Plain Road
Danbury, CT 06811

Cassette Fue Operating Instructions

Note: Always follow the safety instructions affixed to this machine.

Safety Features:

1. In order to prevent gas leaks you must have the *on/off* switch in the *off* position when installing the butane canister.
2. If for any reason an over pressure condition occurs, the flow of gas will be automatically blocked by a fuel safety pin. The flame will extinguish and the canister will displace. If this occurs, remove the canister from the unit and carefully reinstall it.
3. This stove comes equipped with a pressure sensitive gas shut-off control unit, which makes your burner safer to use.

Installing the fuel canister:

1. The compartment for the fuel canister is located on the right side of the stove. Lift the hinged cover to install the canister.
2. Be sure the *on/off* switch is in the *off* position. The fuel canister cannot be locked into position if the control knob is not in the *off* position.
3. Align the arrow on the regulator of the stove so that the collar notch on the can lines up with the receiving tab.
4. Close the cover.
5. Push down the canister control lever to the set position. If the position of the canister is wrong, you will hear a hissing sound that indicates a gas leak. Check the canister for proper placement.
6. After repositioning the canister, reset the fuel canister lock lever to the set position.
7. Assuming the canister is in the correct position, turn the fuel supply knob counter clockwise to the *on* position. You will hear a click that produces a spark and ignites the burner. If the burner does not light, repeat this procedure. During the ignition procedure, if the burner does not light and the fuel supply knob is not in the *off* position, gas will escape and a distinct odor will be present.
8. To regulate the flame, turn fuel knob from the *on* position toward the *off* position until the desired flame height is reached.
9. To shut off, return the fuel knob to the *off* position. Release the fuel canister lever. The unit is now off. Remove the fuel canister from its compartment.

For any questions or concerns, please contact us immediately.

Thank you for your business!